



Upgrade  
your Newline  
Display!



## CHROMEBOX OPS PC

### THE MOST SECURE AND SEAMLESS CHROMEOS EXPERIENCE FOR YOUR DISPLAY

**Upgrade** your **Newline Interactive display** with advanced **Chromebox OPS PC**. Built on the trusted **ChromeOS platform**, this powerful device brings enterprise-grade security, full **Google ecosystem integration**, and outstanding performance to **education** and **corporate** environments. Seamlessly log in with your Google credentials - no separate accounts or setup needed. Whether you're managing **classrooms**, **meeting rooms**, or **digital signage networks**, the Chromebox OPS provides a **streamlined**, **secure**, and **intuitive user experience**. With **Google Play support**, real-time updates, and built-in virus protection, it's designed for **24/7 reliability** and **IT efficiency**. Plus, advanced features like **remote device management** via **Google Admin Console** make it a favorite for system integrators and administrators.

- ✓ ChromeOS Advanced Security
- ✓ Seamless Google Integration
- ✓ 4K2K UHD Playback
- ✓ Wi-Fi 6E

- ✓ Google Play Store Support
- ✓ 24/7 IT Admin Support
- ✓ Simplified Remote Management
- ✓ Built for EDU & Enterprise

**With Chromebox OPS, your Newline display becomes enterprise-ready.**

## MODEL

CHROMEBOX OPS PC	
------------------	--

## SMART SYSTEM

System	Chrome OS
CPU	Intel® Core™ i3-1315U
GPU	Intel® UHD Graphics integrated on CPU
Performance	10M Cache, up to 4,50 GHz
Memory	8 GB (4 GB x 2) DDR4
Storage	256 GB
Wi-Fi	WiFi 6E 802.11 b/g/n/ac/ax
Bluetooth	5.2
LAN	10/100/1000M

## ELECTRICAL

Working Voltage	DC19 V / 5 A
-----------------	--------------

## FRONT I/O

USB-A 3.2	2
USB-A 2.0	2
USB-C	1
HDMI OUT 2.1 (4K@30 Hz)	1
Jack 3,5 mm (Mic In + Line Out)	1
RJ45 10/100/1000 M	1
Power LED	1
Power button	1
Kensington Lock Hole	1

## SPECIAL

Language	Multilanguage Support
Multuser Management	Supported
Trusted Platform Module	Google H1 Chip
Certificates	CE, Reach, ROHS

## NEWLINE SOLUTIONS COMPATIBILITY

Newline Displays	19RS, 19IP, 20ER, 20HO, 20UP, 21IP, 19NT, 21Q, 22Q, 22Z, 23C, 23QA, 23QAS, 23QCA, 23QCA+, 24Z
------------------	---

## TRANSPORTATION / STORAGE

Material	Metal
Temperature	Operating 0°C - 45°C Storage -20°C - 60°C
Humidity	5% - 93% (non-condensing)
Dimmensions	200 x 119 x 30 mm
Packaging Dimmensions	245 x 206 x 65 mm
Net Weight	0,7 Kg
Gross Weight	1 Kg