

newline

NEW 2025



Upgrade
your Newline
Display!



NEWLINE GOOGLE EDLA OPS PC TURN YOUR NEWLINE DISPLAY INTO A CERTIFIED GOOGLE POWERHOUSE

Supercharge your **existing display** with the Newline **Google EDLA Certified OPS** - a seamless, plug-and-play upgrade that brings the full power of **Google** and **Android 15** to your fingertips. Designed for displays without native EDLA certification, this OPS unit transforms your setup into a fully integrated **Google Workspace** environment. Access **Google Docs, Sheets, Slides**, and more - all directly on your Newline interactive display. Collaborate effortlessly, streamline workflows, and enjoy native Google services like never before. With **cutting-edge performance** powered by the **Rockchip processor** and **high-capacity memory**, multitasking and running demanding apps is **smooth** and **reliable**.

No setup hassle - just slot in the OPS and go.

NEWLINE INTERACTIVE ECOSYSTEM

The Newline Interactive Ecosystem empowers users with intuitive tools that seamlessly integrate with any software or device - making collaboration, learning, and presenting effortless.

WHITEBOARD

DISPLAY MANAGEMENT PLUS

SIGNAGE PRO

CAST+

CLASSROOM TOOLS

MODEL

EDLA OPS PC	WB76110A
-------------	----------

SMART SYSTEM

System	Android 15
CPU	RK3588
GPU	ARM Mali-G610 MP4
NPU	6 TOPS
Frequency	4 x Cortex A76 @2.4 GHz 4 x Cortex A55 @2.4 GHz
Memory	16 GB DDR4
Storage	256 GB
Wi-Fi/ BT	Wi-Fi 6 & Bluetooth 5.0
LAN	10/100/1000M

ELECTRICAL

Working Voltage	DC19 V / 5 A
-----------------	--------------

FRONT I/O

USB-A 3.0	3
USB-C	1
RJ45 10/100/1000 M	1
HDMI OUT 2.1 (4K@30 Hz)	1
HDMI IN 2.1 (4K@60 Hz)	1
Jack 3,5 mm Mic In	1
Jack 3,5 mm Line Out	1
Power button	1
Reset button	1
Power LED	1

SPECIAL

Language	Multilanguage Support
OTA	Supported
Multiuser Management	Supported
Certificates	CE, Reach, ROHS

NEWLINE SOLUTIONS COMPATIBILITY

Newline Software Ecosystem	Cast+, Signage Pro, Whiteboard Display Management Plus, Classroom Tools, Vote, Visualizer
Newline Displays	19RS, 19IP, 20ER, 20HO, 20UP, 21IP, 19NT, 21Q, 22Q, 22Z, 23C, 23QA, 23QAS, 23QCA, 23QCA+, 24Z

TRANSPORTATION / STORAGE

Material	Metal
Temperature	Operating 0°C - 45°C Storage -20°C - 70°C
Humidity	5% - 95% (non-condensing)
Dimmensions	180 x 119 x 30 mm
Packaging Dimmensions	270 x 207 x 70 mm
Net Weight	0,76 Kg
Gross Weight	0,9 Kg