



## LA SEMPLICITÀ PENSATA PER OGNI UTENTE

Un display interattivo 4K pronto all'uso. Basta collegare il vostro dispositivo per iniziare: senza configurazioni e senza complicazioni. Con una scrittura simile alla carta, 40 punti di tocco, altoparlanti integrati e connettività Plug and Play tramite USB Type-C, rappresenta una soluzione completa. Progettata per essere facile ed efficace, la Serie C di Newline vi permette di concentrarvi sull'insegnamento o sul lavoro di squadra, non sulla tecnologia.



### SLOT OPS INTEGRATO

Completate il vostro display con un PC OPS integrato, portando Windows direttamente sullo schermo per un'esperienza tutto-in-uno senza interruzioni. Accendetelo e iniziate subito!

### TUTTE LE APP E I VOSTRI FILE, SUBITO PRONTI!

Con la tecnologia **Plug and Play**, basta collegare un unico cavo per trasferire audio, video, alimentazione, dati e comandi touch. Nessuna attesa, iniziate subito a lavorare.



USB di Tipo C



Ampia  
Compatibilità



Risoluzione  
4K HD



Angolo di visione  
massimo



Impianto Audio  
di Alta Qualità



Connettività  
versatile

65"

75"

86"

**MODEL**

C Series 65"	TT-6523C
C Series 75"	TT-7523C
C Series 86"	TT-8623C

**PANEL**

Backlight	Direct LED
Glass Surface	Anti-Glare Glass
Bonding Technology	Certified Zero Bonding
Display Area	65": 1429 x 804 mm
	75": 1651 x 929 mm
	86": 1896 x 1066 mm
Display Ratio	16:9
Resolution	3840 x 2160 (4K)
Colours	1,07 Billion
	65": 450 cd/m <sup>2</sup>
	75": 450 cd/m <sup>2</sup>
Brightness	86": 450 cd/m <sup>2</sup>
Contrast Ratio	4000:1
Response Time	5 ms
Viewing Angle	178°
Display Life Time	≥ 50 000 hours
Transparency	> 88%
Haze	2 % ~ 5 %
Touch Surface Hardness	7 MoHs, Pencil 9H

**POWER CONSUMPTION**

Standard Mode*	65": 91 W
	75": 116 W
	86": 146 W
Standby mode*	<0,5 W

**TOUCH**

Touch Technology	Stellar Touch Technology
Touch Points	40 Windows
	20 Android/MAC/Linux
Touch Screen Writing Tools	Passive pen, Finger, Fist
Number of stylus	2
Accuracy	±1 mm

**SPEAKER**

Speaker Position	Front Facing
Speaker Rated Impedance	6 Ω
Speaker Max.Power Output	15 W x 2

**FRONT I/O**

USB Type-C	1
HDMI IN 2.0 (4k @60 Hz)	1
USB 2.0 Type-B (Touch)	1
USB 3.0 Type-A (Dynamic)	2
Microphone In (Jack 3,5 mm)	1

**REAR I/O**

HDMI IN 2.0 (4k @60 Hz)	2
USB 2.0 Type-B (Touch)	1
USB Type-A 2.0 (Dynamic)	2
USB Type-A 2.0 (Embedded)	1
RS232	1
RJ45 (Gigabit)	In x 1 / Out x 1
OPS Slot	1
SPDIF	1
Audio Line Out (Jack 3,5 mm)	1
VGA In	1
USB Type-C (Camera Slot)	1

**SMART SYSTEM**

SoC Chipset	Arm Cortex-A55 x 4
RAM	2 GB
Total Storage	8 GB
Operating System	No OS

**DIMENSIONS / WEIGHT**

Outline Dimensions* (Excl. wall mount)	65": 1513 x 923 x 110 mm
	75": 1735 x 1048 x 111 mm
	86": 1981 x 1186 x 111 mm
Net Weight*	65": 38,5 Kg
	75": 50 Kg
	86": 74 Kg
VESA*	65": 600 x 400 mm
	75": 800 x 400 mm
	86": 800 x 400 mm

\* Le misure indicate sono approssimative e soggette a modifiche. Non sono ancora considerate definitive.