



## DIRECT VIEW LED IN **LARGE FORMAT**

Experience the power of DV One+, an advanced LED display solution that combines durability with stunning visuals. Built with glue-on-board (GOB) technology, it ensures reliability and low maintenance. With a wide color gamut and a 6000:1 contrast ratio, it delivers lifelike images. Perfect for indoor advertising or conference rooms, DV One+ offers smooth visuals and high refresh rates. Available in large size options, DV One+ makes a statement in any space.



### GO BEYOND WITH CLICK2CAST!

Compatible with the Newline Click2Cast dongle, a hassle-free hardware solution for one click casting. Just a single button to initiate wireless screen casting effortlessly.



### NEWLINE INTERACTIVE ECOSYSTEM

The Newline Interactive Ecosystem streamlines operations with seamless tools for content sharing, signage management, and display control, optimizing workflows

CAST+

DISPLAY MANAGEMENT PLUS



Edge-to-Edge  
Ultra Slim Design



Ultra High  
Refresh Rate



Full HD  
Resolution



Plug & Play



Easy of  
Maintenance



Lightweight  
Construction

135"

163"

189"

## MODEL

DVOne+ 135"	DV-13524Plus
DVOne+ 163"	DV-16324Plus
DVOne+ 189"	DV-18924Plus

## PANEL

Display Type	Direct LED
Lights Welding Type	GOB
Display Area	135": 3000 x 1687,5 mm 163": 3600 x 2025,5 mm 189": 4200 x 2363 mm
Display Ratio	16:9
Resolution	1920 x 1080 (FHD)
Brightness	550 cd/m <sup>2</sup>
Contrast Ratio	6000:1
Pixel pitch	135": 1,56 mm 163": 1,875 mm 189": 2,18 mm
Viewing Angle	160°
Refresh Rate	3840 Hz
Display Life Time	100 000 hours
Operating Temperature	-10°C - 40°C
Operating Humidity	10% - 80% RH No Condensation

## POWER CONSUMPTION

Standard Mode*	135": 580 W 163": 690 W 189": tbc W
Standby mode*	<0,5 W

## SMART SYSTEM

CPU	A311D2
RAM	4 GB
Storage	32 GB
Operating System	AOSP
Wi-Fi	6

## EXTRA FIRMWARE FEATURES

Wake-on-LAN	✓
Wake-on-WiFi	✓

## SPEAKER

Speaker Position	Bottom front
Speaker Max.Power Output	135": 5 W x 1 163": 5 W x 1 189": 5W x 1

## REAR I/O

HDMI IN 2.0 (4K @60 Hz)	1
HDMI OUT 2.0 (4K @60 Hz)	1
USB Type-A 3.0	1
LAN In (RJ45)	1
SPDIF Out	1
Audio Output (Jack 3,5 mm)	1
RS232	1

## SIDE I/O

HDMI IN 2.0 (4K @60 Hz)	1
USB Type-B 2.0	1
USB Type-A 3.0	1
USB Type-C	1

## DIMENSIONS / WEIGHT

Outline Dimensions (Excl. wall mount)	135": 3009 x 1704 x 66 mm 163": 3609 x 2042 x 66 mm 189": 4209 x 2379,5 x 66 mm
Net Weight	135": 152 Kg 163": 209,5 Kg 189": tbc Kg

## NEWLINE SOLUTIONS COMPATIBILITY

Newline Software Ecosystem	Cast+, Signage Pro & Display Mangement Plus
Newline Accessories	Click2Cast

\* The provided measures are indicative and subject to further adjustments. They are not yet considered definitive.