newline

10:24



NEW 2023 Elara is the eighth largest moon of Jupiter. And with a size of only 2% of Europe, the smallest of the four Galilean moons.







Elara Pro, a Google EDLA certified powerhouse, seamlessly integrated with Google Apps. This flexible solution ensures a superior user experience in any workspace. High-precision writing, immersive sound with a subwoofer, NFC-enabled login and hybrid UC redefine collaboration. Reinvent your workspace, setting a new standard in corporate excellence with Elara Pro.

4



MODULAR SYSTEM

Elevate your experience with our universe of solutions. Customise your display with Newlines' accessories. Mix and match to create the perfect fit.

NEWLINE INTERACTIVE ECOSYSTEM

The Newline Interactive Ecosystem enhances productivity with versatile tools that seamlessly integrate with any software or device, meeting all classroom needs.

WHITEBOARD	CAST+	ENGAGE	
CLASSROOM TOOLS		DISPLAY MANAGEMENT	









Secure Multi

User Profiles

Enhanced Wi-Fi & Bluetooth

100 W Powered USB Type-C







Powerful Performance

High Quality Sound incl. Subwoofer

SDM-S Ready



PRODUCT SPECIFICATIONS

ELARAPro

1

1

1

2

1

2

1

3

1

2

1

1

1.8 GHz

 \checkmark

RV40

./

(COOK), FLAC

Out x 1

In x 1 / Out x 1

Rockchip RK3588 octa-core processor, 4x Cortex-A76 at

Mali Odin G610 MC4

320 GB (Expandable)

JPG, JPEG, BMP, PNG MPEG1, MPEG2, MPEG4, SorensonH.263, H.263, H.264,

MVC, AVS, AVS+, WMV3, VC1, Motion JPEG, VP8, VP9, RV30/

MPEG1/2 @LAYER1; @LAYER2; @LAYER3, EAC3, ACC-LC, HEAAC, VORBIS, LPCM, IMA-ADPCM, MS-

ADPCM, G711 A/ MU-LAW, LBR

Integrated (Replaceable)

65": 1513 x 927 x 118 mm

75": 1735 x 1051 x 119 mm

86": 1982 x 1191 x 119 mm

65": 39 Kg

75": 52 Kg 86": 65 Kg

65": 600 x 400 mm

75": 800 x 400 mm

86": 800 x 400 mm

Android 13 Certified

16 GB (DDR4)

2.4GHz, 4x Cortex-A55 cores at

FRONT I/O

USB-A 3.0

REAR I/O

Microphone In

DisplayPort 1.2

USB-B (Touch)

(Powered 15 W) USB-C 3.0

USB -A 3.0 Android HDMI OUT 2.0 (4K @60 Hz)

Power Out Connect (180 W)

USB-C 3.0

USB-A 3.0

RS232 RJ45 (Gigabit)

OPS Slot SPDIF Audio Line Out WIFI Module Slot SDM-S Slot

NFC

GPU

RAM

SMART SYSTEM

SoC Chipset

Total Storage

Google EDLA

Operating System

Formats Support For Image

Formats Support For Video

Formats Support For Audio

Wi-Fi 6 + Bluetooth 5.2 Module

EXTRA FIRMWARE FEATURES

DIMENSIONS / WEIGHT

Outline Dimensions*

(Excl. wall mount)

Net Weight*

VESA*

Multiuser profile Embedded Google Apps

USB Type-C (Powered 100 W)

HDMI IN 2.0 (4K @60 Hz)

HDMI IN 2.0 (4K @60 Hz)

USB-B 3.0 (Touch)

8.4	0		-	
IVI	U	טי	E	L

ELARA Pro 65"	TT-6523QCA+
ELARA Pro 75"	TT-7523QCA+
ELARA Pro 86"	TT-8623QCA+

PANEL

FANLL	
Backlight	Direct LED (Wide Color Gamut + Anti Blue Light)
Glass Surface	Anti-Glare+Anti-Fingerprint, + Antimicrobial Tempered Glass
Bonding Technology	Certified Zero Bonding
Display Area	65": 1428 x 803 mm 75": 1650 x 928 mm 86": 1895 x 1066 mm
Display Ratio	16:09
Resolution	3840 x 2160 (4K)
Colours	1,07 Billion
Brightness	450 cd/m ²
Contrast Ratio	5000:1
Response Time	5 ms
Viewing Angle	178°
Display Life Time	≥ 50 000 hours
Transparency	> 88%
Haze	2 % - 5 %
Touch Surface Hardness	7H

POWER CONSUMPTION

Standard mode*	65": 133 W 75": 150 W 86": 168 W
Standby Mode*	<0,5 W

TOUCH

Touch Technology	Stellar Touch Technology
Touch Points	50 Windows 20 Android/MAC/Linux
Touch Screen Writing Tools	Passive pen, Finger, Fist
Number of stylus	2
Accuracy	±1 mm
Real Palm Rejection	\checkmark

SPEAKER

Speaker Position	Front Facing
Speaker Rated Impedance	6 Ω
Speaker Freq.Response	250 Hz-20 KHz SPL -10 dB
Output S.P.L.	90±3 dB
Speaker Max.Power Output	20 W x 2

SUBWOOFER

Speaker Position	Rear Side
Speaker Rated Impedance	4 Ω
Speaker Freq.Response	20 Hz-20 KHz SPL -10 dB
Output S.P.L.	77±2 dB
Speaker Max.Power Output	20 W x 1

MICROPHONE

(

Mic Possition	8 Microphone Array Upper Front
Pick Up Distance	8 m
Mic Performance	Echo cancellation, Beamforming, Noise Reduction

15°

Newline-interactive.com/eu

Included (ModCam+)

120° FOV Lenses

3840 × 2160/ 30 fps (4K)

AI CAMERA MODULE

Camera Camera Resolution Field of View Camera Tile Range

* The provided measures are indicative and subject to further adjustments. They are not yet considered definitive.

newline

Contact us at: Info_eu@newline-interactive.com / Support_eu@newline-interactive.com / Technical Support Hotline: +34 91 804 31 79

2023 Newline Interactive Europe S.L. All Rights Reserved, Newline logo is a registered trademark in the United States and other countries around the world. Product specifications may vary by region, please contact our local offices for details. All weights and dimensions are approximate. Actual product features and specifications are subject to change without notice. This material may include corporate names and trademarks of third parties which are the properties of the third parties respectively.